

Features / Cutter head type	ART 140	ART 160	ART 180	ART 240	ART 280	ART 350	ART 400	ART 800	ART 100LS	ART 110LS	ART 200LS	ART 300LS
Height (mm)	650	840	840	1420	1420	1400	1700	1800	720	830	1200	1450
Width (mm)	410	650	650	1000	1000	1000	1700	1540	380	500	500	600
Depth (mm)	390	460	460	620	680	680	1000	925	320	500	500	680
Engine Displacement (ml/r)	398	1340	1340	2099	2812	4198	8396	20000	750	1340	2812	4198
Speed range (r/min)	0-90	0-90	0-130	0-85	0-90	0-140	0-80	0-90	0-95	90	0-95	0-80
Max Flow (L/min)	47	174	174	280	337	580	670	1800	60	236	400	400
Rated Pressure (MPa)	28	25	25	25	28	30	30	35	28	28	28	30
Max Pressure (Mpa)	40	30	30	35	45	45	45	45	35	35	45	40
Max Torque (N.m)	3200	5200	6800	12800	16000	23500	46500	111300	3600	7500	12800	23500
Max Power (KW)	40	45	55	65	110	120	200	400	30	50	70	120
Cutter Head (pcs)	32	36-56	36-56	48	56	76	76	84	18	32	32	30
Excavator Weight (T)	5-10	10-15	18-22	20-30	30-40	30-50	40-60	80-120	6-10	10-15	20-30	20-40
Cutter Head type	20-22	DT24/16	DT24/16	30	30	30-35	30-38	30-38	22	24	24	30